

View Online at <https://aerobasegroup.com/nsn/5340-00-178-6593>

Mounting Hole Type:

Countersunk

First Leg Length:

Between 0.740 inches and 0.800 inches

Second Leg Length:

Between 1.680 inches and 1.740 inches

Second Leg Width:

Between 2.970 inches and 3.030 inches

First Leg Hole Diameter:

Between 0.208 inches and 0.214 inches

Second Leg Hole Diameter:

Between 0.146 inches and 0.176 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 0.372 inches and 0.392 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

Between 0.372 inches and 0.392 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 1.078 inches and 1.158 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.780 inches and 0.840 inches

First Leg Thickness:

Between 0.080 inches and 0.100 inches

Second Leg Thickness:

Between 0.080 inches and 0.100 inches

Center Section Height:

Between 3.020 inches and 3.080 inches

Center Section Width:

Between 2.970 inches and 3.030 inches

Center Section Thickness:

Between 0.080 inches and 0.100 inches

First Leg Width:

Between 2.970 inches and 3.030 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.970 inches and 2.030 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Center hole 0.483 in. Min, 0.490 in. Maximum dia

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, 0 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0