

View Online at <https://aerobasegroup.com/nsn/5340-00-181-1339>

**Overall Length:**

Between 5.271 inches and 5.291 inches

**Material Thickness:**

0.062 inches

**Mounting Hole Diameter:**

Between 0.127 inches and 0.133 inches

**Mounting Hole Quantity:**

3

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.690 inches and 0.710 inches

**Performance Type:**

Not rated

**Reversible Feature:**

Not included

**Hinge Pin:**

Not included

**Knuckle Quantity:**

6

**Knuckle Length:**

Between 0.491 inches and 0.495 inches

**End Knuckle Length:**

Between 0.350 inches and 0.370 inches

**Pin Center To Body Edge Distance:**

Between 0.865 inches and 0.885 inches

**Knuckle Inside Diameter:**

Between 0.093 inches and 0.098 inches

**Knuckle Type:**

Friction

**Material And Location:**

Steel, ams 5612

**Surface Treatment And Location:**

Passivated, gss7021, grumman aerospace corporation

**Special Features:**

One end, knuckle lg, 0.491 in. Min, 0.495 in. Max, chamfered from knuckle end to outside edge, 0.446 in. Min, 0.466 in. Max

**Style Designator:**

Butt parallel holes

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25100