

View Online at <https://aerobasegroup.com/nsn/5340-00-181-1339>

Overall Length:

Between 5.271 inches and 5.291 inches

Material Thickness:

0.062 inches

Mounting Hole Diameter:

Between 0.127 inches and 0.133 inches

Mounting Hole Quantity:

3

Center To Center Distance Between Mounting Holes Along Length:

Between 0.690 inches and 0.710 inches

Performance Type:

Not rated

Reversible Feature:

Not included

Hinge Pin:

Not included

Knuckle Quantity:

6

Knuckle Length:

Between 0.491 inches and 0.495 inches

End Knuckle Length:

Between 0.350 inches and 0.370 inches

Pin Center To Body Edge Distance:

Between 0.865 inches and 0.885 inches

Knuckle Inside Diameter:

Between 0.093 inches and 0.098 inches

Knuckle Type:

Friction

Material And Location:

Steel, ams 5612

Surface Treatment And Location:

Passivated, gss7021, grumman aerospace corporation

Special Features:

One end, knuckle lg, 0.491 in. Min, 0.495 in. Max, chamfered from knuckle end to outside edge, 0.446 in. Min, 0.466 in. Max

Style Designator:

Butt parallel holes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25100