

View Online at <https://aerobasegroup.com/nsn/5340-00-182-3990>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.516 inches rod connection and 0.610 inches rod connection

**Shank Length:**

Between 2.095 inches and 2.235 inches

**Hole Diameter:**

Between 0.187 inches and 0.190 inches

**Shank Diameter:**

0.250 inches

**Overall Height:**

Between 0.490 inches and 0.510 inches

**Overall Width:**

Between 0.284 inches and 0.329 inches

**End Radius:**

Between 0.280 inches and 0.340 inches

**Fork Span Width:**

Between 0.104 inches and 0.109 inches

**Securing Pin Hole Diameter:**

Between 0.046 inches and 0.056 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 2.335 inches and 2.415 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 3.025 inches and 3.045 inches

**Fork Arm Thickness:**

0.090 mils and 0.110 inches

**Thread Size:**

0.250 inches rod connection

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

299-099-0311, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0