

View Online at <https://aerobasegroup.com/nsn/5340-00-182-3990>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.516 inches rod connection and 0.610 inches rod connection

Shank Length:

Between 2.095 inches and 2.235 inches

Hole Diameter:

Between 0.187 inches and 0.190 inches

Shank Diameter:

0.250 inches

Overall Height:

Between 0.490 inches and 0.510 inches

Overall Width:

Between 0.284 inches and 0.329 inches

End Radius:

Between 0.280 inches and 0.340 inches

Fork Span Width:

Between 0.104 inches and 0.109 inches

Securing Pin Hole Diameter:

Between 0.046 inches and 0.056 inches

Distance From Center Of Securing Pin Hole To Rod End:

Between 2.335 inches and 2.415 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 3.025 inches and 3.045 inches

Fork Arm Thickness:

0.090 mils and 0.110 inches

Thread Size:

0.250 inches rod connection

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

299-099-0311, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0