

View Online at <https://aerobasegroup.com/nsn/5340-00-182-9804>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Countersunk

First Leg Length:

0.690 inches

Second Leg Length:

5.000 inches

Second Leg Width:

6.968 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

0.218 inches

Second Leg Distance Between Hole Centers Along Width:

3.000 inches

Second Leg Distance Between Hole Centers Along Length:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.466 inches

First Leg Thickness:

0.093 inches

Second Leg Thickness:

0.093 inches

First Leg Width:

6.968 inches

First Leg Distance Between Hole Centers Along Width:

4.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.480 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 302

Material Specification:

Qq-s-766 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.