NSN 5340-00-187-4569

Mounting Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-187-4569

	_
Special	Features

Aluminum alloy casting, mil-a-21108, alloy a356, t6, class 10, 1 hole 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Dia with 5.0 degree taper through 0.800 in.Deep, 2 holes 0.340 in.Deep, 3 holes 0.3	0.400
in.Dia with 5.0 degree taper through 0.330 in.Deep, 3.740 in.O/a lg, 2.000 in.O/a w, 0.800 in.O/a h, for inner rear support mtg	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0