NSN 5340-00-192-4136

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-192-4136

Fabrication Method (non-core):	
Machined	
First Leg Length:	
Between 0.630 inches and 0.670 inches	
Second Leg Length:	
Between 0.630 inches and 0.670 inches	
Second Leg Width:	
Between 0.485 inches and 0.515 inches	
First Leg Hole Diameter:	
Between 0.214 inches and 0.224 inches	
Second Leg Hole Diameter:	
Between 0.214 inches and 0.224 inches	
Second Leg Distance From Edge To Hole Center Along W	idth:
Between 0.240 inches and 0.260 inches	
Second Leg Distance From Edge To Hole Center Along Le	ength
Between 0.240 inches and 0.260 inches	-
First Leg Thickness:	
Between 0.056 inches and 0.062 inches	
Second Leg Thickness:	
Between 0.056 inches and 0.062 inches	
Center Section Height:	
Between 0.591 inches and 0.617 inches	
Center Section Width:	
Between 0.485 inches and 0.515 inches	
Center Section Thickness:	
Between 0.056 inches and 0.062 inches	
First Leg Width:	
Between 0.485 inches and 0.515 inches	
First Leg Distance From Edge To Hole Center Along Width	h:
Between 0.240 inches and 0.260 inches	
First Leg Distance From Edge To Hole Center Along Leng	th:
Between 0.240 inches and 0.260 inches	
First Leg End Radius:	
Between 0.344 inches and 0.406 inches	
Second Leg End Radius:	
Between 0.344 inches and 0.406 inches	
First Leg Style:	
End radius	
First Leg Hole Arrangement Style:	
One hole	
Second Leg Style:	

NSN 5340-00-192-4136

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

119.0 degrees

Second Leg Angle:

119.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0