# NSN 5340-00-193-9047

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-193-9047

TL			$\sim$	200	
ın	ros	_		266	•

2b left internal (includes through thread)2a right external

#### **Thread Direction:**

Right-hand right external

## Thread Length:

0.140 inches left internal (includes through thread)0.200 inches right external

#### Flange Diameter:

Between 0.159 inches and 0.161 inches

#### Flange Thickness:

Between 0.178 inches and 0.182 inches

#### Length:

Between 0.468 inches and 0.488 inches

#### Thready Qty Per Inch (tpi):

56 left internal (includes through thread)

#### **Thread Size:**

0.086 inches right external

#### **Special Features:**

Slot drive 0.030 inch. Wide and 0.030 inch. Deep on stud end

#### Material:

Steel comp 303 standoff

# **Material Specification:**

Astm a582 assn standard single material response standoff

#### **Surface Treatment:**

Passivate standoff

# **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response standoff

## **Style Designator:**

Flanged with left internal thread

# **Thread Series Designator:**

Unc right external

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A08900