NSN 5340-00-195-2070

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-195-2070

Mounting Hole Type:

Plain

First Leg Length:

Between 0.570 inches and 0.610 inches

Second Leg Length:

Between 0.570 inches and 0.610 inches

Second Leg Width:

2.511 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Hole Diameter:

Between 0.230 inches and 0.250 inches

Second Leg Hole Diameter:

Between 0.230 inches and 0.250 inches

Second Leg Distance Between Hole Centers Along Width:

2.011 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

0.400 inches

Second Leg Thickness:

0.040 inches

Center Section Height:

Between 0.310 inches and 0.350 inches

Center Section Width:

2.010 inches

Center Section Thickness:

0.040 inches

First Leg Width:

1.500 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Style:

Corner radius

NSN 5340-00-195-2070Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
Between 0.07 radians and 0.12 radians
Second Leg Angle:
Between 0.07 radians and 0.12 radians
Material:
Steel
Material Specification:
Ams 5504 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A042a0