

View Online at <https://aerobasegroup.com/nsn/5340-00-201-1052>

Fabrication Method (non-core):

Formed

First Leg Length:

Between 0.420 inches and 0.440 inches

Second Leg Length:

Between 0.420 inches and 0.440 inches

Second Leg Width:

Between 0.485 inches and 0.515 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.056 inches and 0.069 inches

Second Leg Thickness:

Between 0.056 inches and 0.069 inches

Center Section Height:

Between 1.324 inches and 1.344 inches

Center Section Width:

Between 0.485 inches and 0.515 inches

Center Section Thickness:

Between 0.056 inches and 0.069 inches

First Leg Width:

Between 0.485 inches and 0.515 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.240 inches and 0.260 inches

Second Leg End Radius:

Between 0.240 inches and 0.260 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

83.0 degrees

Second Leg Angle:

120.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0