

View Online at <https://aerobasegroup.com/nsn/5340-00-205-5607>

**Center To Center Distance Between Bolt Holes Along Width:**

Between 4.860 inches and 4.890 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 6.735 inches and 6.765 inches

**Wheel Quantity:**

2

**Safe Operating Load Rating:**

2400.0 pounds

**Material And Location:**

Rubber tread err-100 err-100

**Unpackaged Unit Weight:**

52.700 pounds

**Wheel Type:**

Built up

**Wheel Diameter:**

10.000 inches

**Effective Height:**

Between 13.750 inches and 14.250 inches

**Features Provided:**

Shock absorber

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Tapered roller

**Swivel Bearing Type:**

Ball

**Swivel Bearing Arrangement:**

One row

**King Bolt Bearing Type:**

Roller

**Tread Width:**

3.250 inches

**Caster Plate Length:**

8.250 inches

**Caster Plate Width:**

7.000 inches

**Caster Plate Mounting Hole Diameter:**

0.625 inches

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25600