

View Online at <https://aerobasegroup.com/nsn/5340-00-209-3606>

Thread Class:

2a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.500 inches rod connection

Shank Length:

Between 0.860 inches and 0.890 inches

Hole Diameter:

Between 0.187 inches and 0.191 inches

Shank Diameter:

0.375 inches

Overall Height:

Between 0.555 inches and 0.565 inches

Overall Width:

Between 0.520 inches and 0.550 inches

Fork Span Width:

Between 0.285 inches and 0.295 inches

Rod Connection Bore Diameter:

Between 0.127 inches and 0.131 inches

Securing Pin Hole Diameter:

Between 0.050 inches and 0.060 inches

Rod Connection Bore Depth:

Between 0.920 inches and 0.950 inches

Distance From Center Of Securing Pin Hole To Rod End:

Between 0.530 inches and 0.560 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 1.590 inches and 1.610 inches

Fork Arm Thickness:

0.120 mils and 0.126 centimeters

Fork Depth:

Between 0.560 inches and 0.585 inches

Distance From Pivot Pinhole Center To Fork End:

Between 0.290 inches and 0.340 inches

Thread Size:

0.375 inches rod connection

Material:

Steel comp 303

Material Specification:

Astm a582, cond b assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0