

View Online at <https://aerobasegroup.com/nsn/5340-00-209-3606>

**Thread Class:**

2a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.500 inches rod connection

**Shank Length:**

Between 0.860 inches and 0.890 inches

**Hole Diameter:**

Between 0.187 inches and 0.191 inches

**Shank Diameter:**

0.375 inches

**Overall Height:**

Between 0.555 inches and 0.565 inches

**Overall Width:**

Between 0.520 inches and 0.550 inches

**Fork Span Width:**

Between 0.285 inches and 0.295 inches

**Rod Connection Bore Diameter:**

Between 0.127 inches and 0.131 inches

**Securing Pin Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Rod Connection Bore Depth:**

Between 0.920 inches and 0.950 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.530 inches and 0.560 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 1.590 inches and 1.610 inches

**Fork Arm Thickness:**

0.120 mils and 0.126 centimeters

**Fork Depth:**

Between 0.560 inches and 0.585 inches

**Distance From Pivot Pinhole Center To Fork End:**

Between 0.290 inches and 0.340 inches

**Thread Size:**

0.375 inches rod connection

**Material:**

Steel comp 303

**Material Specification:**

Astm a582, cond b assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0