

View Online at <https://aerobasegroup.com/nsn/5340-00-220-2614>

**End Application:**

W/s: missile, minuteman lgm-30

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

1500.0 pounds

**Material And Location:**

Steel wheel rim err-100 err-100

**Unpackaged Unit Weight:**

16.500 pounds

**Wheel Type:**

Built up

**Wheel Diameter:**

8.000 inches

**Effective Height:**

9.750 inches

**Features Provided:**

Axle lubrication fitting and brake lock and spanner bushing and swivel lock and swivel lubrication fitting

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller

**Swivel Bearing Type:**

Ball

**Swivel Bearing Arrangement:**

One row

**King Bolt Bearing Type:**

Tapered roller

**Tread Width:**

2.000 inches

**Caster Plate Length:**

6.500 inches

**Caster Plate Width:**

4.500 inches

**Center To Center Major Distance Between Mounting Slots Along Length:**

5.250 inches

**Center To Center Minor Distance Between Mounting Slots Along Length:**

4.938 inches

**Center To Center Major Distance Between Mounting Slots Along Width:**

3.375 inches

**Center To Center Minor Distance Between Mounting Slots Along Width:**

2.438 inches

**Caster Plate Mounting Slot Width:**

0.500 inches

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25600