

View Online at <https://aerobasegroup.com/nsn/5340-00-220-2773>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.880 inches

Second Leg Length:

1.160 inches

Second Leg Width:

2.000 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance Between Hole Centers Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.510 inches

First Leg Thickness:

Between 0.083 inches and 0.103 inches

Second Leg Thickness:

Between 0.083 inches and 0.103 inches

First Leg Width:

2.360 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

1.860 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

0.867 in. Radius in first leg between the two holes

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0