

View Online at <https://aerobasegroup.com/nsn/5340-00-221-5469>

Fabrication Method (non-core):

Cast

Mounting Hole Type:

Counterbored

First Leg Length:

2.375 inches

Second Leg Length:

2.438 inches

Reinforcement Method (non-core):

Web center section

Second Leg Width:

5.500 inches

Second Leg End Width:

2.750 inches

Second Leg Hole Diameter:

Between 0.875 inches and 0.877 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.062 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

5.500 inches

First Leg Corner Radius:

0.250 inches

First Leg Style:

Corner radius

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg has 5 holes: 2 holes, 0.250 in. Dia, center-to-center distance between holes 4.125 in.; 2 holes directly below, 0.376 in. Min, 0.396 in. Maximum dia, center-to-center distance between holes 4.125 in.; 1 hole, 0.125 in. Dia, located at dead center

Material:

Aluminum alloy 535.0

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-i-8625, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-i-8625 spec.