

View Online at <https://aerobasegroup.com/nsn/5340-00-225-1384>

**Center To Center Distance Between Bolt Holes Along Width:**

4.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

5.500 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

500.0 pounds

**Material And Location:**

Rubber tread err-100 err-100

**Surface Treatment And Location:**

Enamel, mil-e-7729-canceled wheel rim and enamel, mil-e-7729-canceled body and enamel, mil-e-7729-canceled plate

**Wheel Type:**

Built up

**Wheel Diameter:**

10.000 inches

**Effective Height:**

13.750 inches

**Features Provided:**

Brake lock and shock absorber

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Tapered roller

**Swivel Bearing Type:**

Roller

**Swivel Bearing Arrangement:**

One row

**King Bolt Bearing Type:**

Roller

**Disassembly Capability:**

Provided

**Tread Width:**

2.500 inches

**Caster Plate Length:**

6.750 inches

**Caster Plate Width:**

5.880 inches

**Caster Plate Mounting Hole Diameter:**

0.500 inches

**Special Features:**

Yellow, fed standard 595, no. 13538, over zinc chromate, mil-p-6689 over oxide film, mil-c-5541

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600