

View Online at <https://aerobasegroup.com/nsn/5340-00-225-1384>

Center To Center Distance Between Bolt Holes Along Width:

4.625 inches

Center To Center Distance Between Bolt Holes Along Length:

5.500 inches

Wheel Quantity:

1

Safe Operating Load Rating:

500.0 pounds

Material And Location:

Rubber tread err-100 err-100

Surface Treatment And Location:

Enamel, mil-e-7729-canceled wheel rim and enamel, mil-e-7729-canceled body and enamel, mil-e-7729-canceled plate

Wheel Type:

Built up

Wheel Diameter:

10.000 inches

Effective Height:

13.750 inches

Features Provided:

Brake lock and shock absorber

Plate Style:

Rectangular

Wheel Bearing Type:

Tapered roller

Swivel Bearing Type:

Roller

Swivel Bearing Arrangement:

One row

King Bolt Bearing Type:

Roller

Disassembly Capability:

Provided

Tread Width:

2.500 inches

Caster Plate Length:

6.750 inches

Caster Plate Width:

5.880 inches

Caster Plate Mounting Hole Diameter:

0.500 inches

Special Features:

Yellow, fed standard 595, no. 13538, over zinc chromate, mil-p-6689 over oxide film, mil-c-5541

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600