

View Online at <https://aerobasegroup.com/nsn/5340-00-229-5815>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.234 inches and 1.266 inches

Second Leg Length:

Between 1.734 inches and 1.766 inches

Second Leg Width:

Between 1.995 inches and 2.005 inches

First Leg Hole Diameter:

Between 0.196 inches and 0.205 inches

Second Leg Hole Diameter:

Between 0.196 inches and 0.205 inches

Second Leg Distance Between Upper Hole Centers Along Width:

Between 1.120 inches and 1.130 inches

Second Leg Distance Between Hole Centers Along Length:

Between 0.932 inches and 0.942 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 0.995 inches and 1.005 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.422 inches and 0.453 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.339 inches and 0.349 inches

First Leg Thickness:

Between 0.118 inches and 0.132 inches

Second Leg Thickness:

Between 0.118 inches and 0.132 inches

First Leg Width:

Between 1.995 inches and 2.005 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.495 inches and 0.505 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.547 inches and 0.578 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0