

View Online at <https://aerobasegroup.com/nsn/5340-00-231-6535>

First Leg Length:

0.560 inches

Second Leg Length:

1.170 inches

Second Leg Width:

1.100 inches

Second Leg Corner Radius:

0.200 inches

First Leg Hole Diameter:

Between 0.184 inches and 0.190 inches

Second Leg Hole Diameter:

Between 0.184 inches and 0.190 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.695 inches and 0.705 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.200 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

1.100 inches

First Leg Corner Radius:

0.200 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.695 inches and 0.705 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.