

View Online at <https://aerobasegroup.com/nsn/5340-00-231-6535>

**First Leg Length:**

0.560 inches

**Second Leg Length:**

1.170 inches

**Second Leg Width:**

1.100 inches

**Second Leg Corner Radius:**

0.200 inches

**First Leg Hole Diameter:**

Between 0.184 inches and 0.190 inches

**Second Leg Hole Diameter:**

Between 0.184 inches and 0.190 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.695 inches and 0.705 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.200 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.200 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

1.100 inches

**First Leg Corner Radius:**

0.200 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.695 inches and 0.705 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.200 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.200 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.