## NSN 5340-00-236-3049

Angle Bracket - Page 1 of 2



First Leg Length:1.500 inchesSecond Leg Length:1.500 inchesSecond Leg Width:2.562 inchesSecond Leg End Width:1.000 inchesFirst Leg Hole Diameter:0.312 inchesFirst Leg Thickness:0.188 inchesSecond Leg Thickness:0.188 inchesSecond Leg Thickness:0.188 inchesFirst Leg Width:2.562 inchesFirst Leg Width:2.562 inchesFirst Leg Distance Between Hole Centers Along Width:0.500 inchesFirst Leg Distance From Edge To Hole Center Along Length:0.500 inchesFirst Leg Distance From Edge To Hole Center Along Length:0.500 inchesFirst Leg Distance From Edge To Hole Center Along Length:0.500 inchesFirst Leg Nole Arrangement Style:SquareFirst Leg Angle:90.0 degreesSpecial Features:One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 rMaterial:SteelStyle Designator:Angle	View Online at https://aerobasegroup.com/nsn/5340-00-236-3049	9
Second Leg Length: 1.500 inches Second Leg Width: 2.562 inches Second Leg End Width: 1.000 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 rf Material: Steel	First Leg Length:	
1.500 inches Second Leg Width: 2.562 inches Second Leg End Width: 1.000 inches First Leg Hole Diameter: 0.312 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	1.500 inches	
Second Leg Width: 2.562 inches Second Leg End Width: 1.000 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Hole Arrangement Style: Square First Leg Hole Arrangement Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	Second Leg Length:	
2.562 inches Second Leg End Width: 1.000 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Alge: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 m Material: Steel Style Designator:	1.500 inches	
Second Leg End Width: 1.000 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 Ig welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	Second Leg Width:	
1.000 inches First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 Ig welded to 2nd leg, internally thd 0.375-18 m Material: Steel Style Designator:	2.562 inches	
First Leg Hole Diameter: 0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	Second Leg End Width:	
0.312 inches First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	1.000 inches	
First Leg Thickness: 0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Hole Diameter:	
0.188 inches Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	0.312 inches	
Second Leg Thickness: 0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Thickness:	
0.188 inches First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	0.188 inches	
First Leg Width: 2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	Second Leg Thickness:	
2.562 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	0.188 inches	
First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Width:	
<ul> <li>1.500 inches</li> <li>First Leg Distance From Edge To Hole Center Along Width:</li> <li>0.500 inches</li> <li>First Leg Distance From Edge To Hole Center Along Length:</li> <li>0.500 inches</li> <li>First Leg Style:</li> <li>Square</li> <li>First Leg Hole Arrangement Style:</li> <li>Two holes</li> <li>Second Leg Style:</li> <li>Square and tapered</li> <li>First Leg Angle:</li> <li>90.0 degrees</li> <li>Special Features:</li> <li>One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r</li> <li>Material:</li> <li>Steel</li> <li>Style Designator:</li> </ul>	2.562 inches	
First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Distance Between Hole Centers Along Width:	
0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	1.500 inches	
First Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Distance From Edge To Hole Center Along Width:	
0.500 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	0.500 inches	
First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Distance From Edge To Hole Center Along Length:	
Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	0.500 inches	
First Leg Hole Arrangement Style: Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Style:	
Two holes Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	Square	
Second Leg Style: Square and tapered First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Hole Arrangement Style:	
Square and tapered <b>First Leg Angle:</b> 90.0 degrees <b>Special Features:</b> One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r <b>Material:</b> Steel <b>Style Designator:</b>	Two holes	
First Leg Angle: 90.0 degrees Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	Second Leg Style:	
90.0 degrees <b>Special Features:</b> One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r <b>Material:</b> Steel <b>Style Designator:</b>	Square and tapered	
Special Features: One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	First Leg Angle:	
One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.375-18 r Material: Steel Style Designator:	90.0 degrees	
Material: Steel Style Designator:	Special Features:	
Steel Style Designator:	One pipe connector 1.500 lg welded to 2nd leg, internally thd 0.33	75-18 npt
Style Designator:	Material:	
	Steel	
Angle	Style Designator:	
	Angle	
Shelf Life:	Shelf Life:	
N/a	N/a	
Unit Of Measure:	Unit Of Measure:	

No

## **NSN 5340-00-236-3049** Angle Bracket - Page 2 of 2

Fiig: A042a0

