NSN 5340-00-239-2244

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-239-2244

| Cro | ss Sectional Shape: |
|-------|---|
| Circ | ular recess |
| Insi | de Diameter: |
| Betv | ween 0.530 inches and 0.550 inches |
| Flar | nge Thickness: |
| 0.02 | 20 inches |
| Out | side Diameter: |
| Betv | ween 0.825 inches and 0.845 inches |
| Edg | je Shape: |
| Rou | ind, no holes |
| Firs | t Recess Inside Height: |
| 0.22 | 20 inches |
| Insi | de Corner Radius: |
| 0.12 | 20 inches |
| Bod | ly Thickness: |
| 0.02 | 20 inches |
| Sec | uring Device Type: |
| Spri | ng clip |
| Fea | tures Provided: |
| Sea | ling capability |
| Mat | erial: |
| Alur | ninum alloy 5052 |
| Mat | erial Specification: |
| Qq-a | a-250/8 federal specification single material response |
| Sur | face Treatment: |
| Ano | dize |
| Sur | face Treatment Specification: |
| Mil-a | a-8625, type 2, cl 1 military specification single treatment response |
| Fsc | Application Data: |
| Bral | ke, multiple disk, aircraft |
| She | If Life: |
| N/a | |
| Unit | t Of Measure: |
| | |
| Den | nilitarization: |
| No | |
| Fiig | : |
| A53 | 1c0 |
| Mil- | std (military Standard): |
| Mil-a | a-8625 spec. |
| | |