## NSN 5340-00-242-6795

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-242-6795

Fabrication Method (non-core):
Formed
First Leg Length:
0.415 inches
Second Leg Length:
0.813 inches
Second Leg Width:
0.688 inches
First Leg Hole Diameter:
0.125 inches
Second Leg Hole Diameter:
0.125 inches
Second Leg Distance Between Hole Centers Along Length:
0.437 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.563 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.125 inches
First Leg Thickness:
0.040 inches
Second Leg Thickness:
0.040 inches
Center Section Height:
0.375 inches
Center Section Width:
0.688 inches
Center Section Thickness:
0.040 inches
First Leg Width:
0.688 inches
First Leg Distance Between Hole Centers Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Width:
0.219 inches
First Leg Distance From Edge To Hole Center Along Length:
0.188 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square

## NSN 5340-00-242-6795

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Heat Treatment:
H-14 strain hardened, 1/2 hard
Material:
Aluminum alloy
Material Specification:
Qq-a-359 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.