

View Online at <https://aerobasegroup.com/nsn/5340-00-252-6950>

Mounting Hole Type:

Threaded and countersunk

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

0.263 mils and 0.267 centimeters

Second Leg Hole Diameter:

0.437 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

0.687 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

0.687 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Width:

2.250 inches

First Leg Distance Between Hole Centers Along Length:

1.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.425 inches

First Leg Distance From Edge To Hole Center Along Length:

0.425 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Additional hole in first leg

Material:

Aluminum

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.