## NSN 5340-00-255-4387



Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-00-255-4387 First Leg Length: 1.000 inches Second Leg Length: 5.750 inches Second Leg Width: 6.000 inches First Leg Hole Diameter: 0.312 inches Second Leg Hole Diameter: 0.104 inches Second Leg Distance Between Hole Centers Along Width: 5.625 inches Second Leg Distance Between Hole Centers Along Length: 4.750 inches Second Leg Distance From Edge To Hole Center Along Width: 0.188 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.188 inches First Leg Thickness: 0.119 inches Second Leg Thickness: 0.119 inches First Leg Width: 6.000 inches First Leg Distance Between Hole Centers Along Width: 4.750 inches First Leg Distance From Edge To Hole Center Along Width: 0.625 inches First Leg Distance From Edge To Hole Center Along Length: 0.625 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes

Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

## NSN 5340-00-255-4387

Angle Bracket - Page 2 of 2

Mil-t-704 spec.



Special Features:
Second leg 2 holes 0.719 in. Dia, 2 holes 0.203 in. Dia, 8 holes 0.156 in. Dia
Material:
Steel
Material Specification:
Astm a415 assn standard single material response
Surface Treatment:
Paint
Surface Treatment Specification:
Mil-t-704, type 4 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):