

View Online at <https://aerobasegroup.com/nsn/5340-00-255-5600>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.549 inches rod connection

Shank Length:

0.406 inches

Hole Diameter:

Between 0.125 inches and 0.127 inches

Shank Diameter:

0.408 inches

Overall Height:

2.045 inches

Overall Width:

Between 1.239 inches and 1.241 inches

Fork Span Width:

Between 0.640 inches and 0.650 inches

Rod Connection Bore Diameter:

Between 0.559 inches and 0.561 inches

Securing Pin Hole Diameter:

Between 0.108 inches and 0.112 inches

Rod Connection Bore Depth:

0.030 inches

Distance From Pivot Pinhole Center To Rod Connection End:

2.130 inches

Fork Arm Thickness:

0.600 inches

Fork Depth:

Between 0.915 inches and 0.925 inches

Shank Shoulder Diameter:

0.560 inches

Shank Shoulder Length:

Between 0.935 inches and 0.941 inches

Distance From Pivot Pinhole Center To Fork End:

Between 0.160 inches and 0.182 inches

Thread Size:

0.375 inches rod connection

Special Features:

Chamfer rod end 0.030 by 45 degrees and undercut 0.060 in. Wide by 0.030 in. Deep

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 3, class 2 federal specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf securing pin hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A264a0

Mil-std (military Standard):

Mil-s-6758 spec.