

View Online at <https://aerobasegroup.com/nsn/5340-00-256-1411>

Fabrication Method (non-core):

Machined

First Leg Length:

0.640 inches

Second Leg Length:

0.702 inches

Second Leg Width:

Between 0.515 inches and 0.546 inches

First Leg Slot Length:

Between 0.255 inches and 0.267 inches

First Leg Slot Width:

Between 0.215 inches and 0.220 inches

Second Leg Hole Diameter:

0.062 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.248 inches and 0.252 inches

Second Leg Distance Between Hole Centers Along Length:

Between 0.248 inches and 0.252 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.125 inches and 0.156 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.156 inches and 0.187 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 0.515 inches and 0.546 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.260 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

0.166 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Paint

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0