NSN 5340-00-269-1611

Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-00-269-1611

Fabrication Method (non-core):

Machined

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

1.500 inches

Second Leg Width:

2.350 inches

Second Leg End Width:

1.850 inches

First Leg Hole Diameter:

0.339 inches

Second Leg Hole Diameter:

Between 0.453 inches and 0.463 inches

Second Leg Distance Between Hole Centers Along Width:

0.885 inches

Second Leg Distance Between Hole Centers Along Length:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.870 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

2.350 inches

First Leg Distance Between Hole Centers Along Width:

1.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.875 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends



NSN 5340-00-269-1611

Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

1st hole 0.189 to 0.195 in. Diameter in line with mating part

Material:

Aluminum alloy

Material Specification:

Qq-a-200/8, 6061, t6 federal specification 1st material response or mil-c-11866, 356-t6 military specification 2nd material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-11866 spec.