

View Online at <https://aerobasegroup.com/nsn/5340-00-269-1971>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.500 inches rod connection

Hole Diameter:

Between 0.375 inches and 0.376 inches

Shank Diameter:

Between 0.451 inches and 0.456 inches

Overall Width:

1.072 inches

Fork Span Width:

Between 0.812 inches and 0.817 inches

Distance From Pivot Pinhole Center To Rod Connection End:

3.700 inches

Fork Arm Thickness:

0.130 inches

Fork Depth:

1.200 inches

Distance From Pivot Pinhole Center To Fork End:

0.370 inches

Thread Size:

0.500 inches rod connection

Special Features:

Has locking device on thds along lg, 0.095 in. By 1.590 in. Lg

Material:

Steel comp 321

Material Specification:

Ams 5645 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A264a0

Mil-std (military Standard):

Mil-s-5002 spec.