NSN 5340-00-275-4667

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-275-4667

Fabrication Method (non-core):
Machined
Mounting Hole Type:
Plain
First Leg Length:
1.500 inches
Second Leg Length:
1.500 inches
Second Leg Width:
2.350 inches
Second Leg End Width:
1.850 inches
First Leg Hole Diameter:
0.339 inches
Second Leg Hole Diameter:
Between 0.189 inches and 0.195 inches
Second Leg Distance Between Hole Centers Along Width:
0.885 inches
Second Leg Distance Between Hole Centers Along Length:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.750 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
First Leg Width:
2.350 inches
First Leg Distance Between Hole Centers Along Width:
1.125 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
0.875 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Chamfered ends

NSN 5340-00-275-4667 Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Special Features:
1 hole on 2nd leg 0.453 to 0.463dia in line with mating part
Material:
Aluminum alloy
Material Specification:
Qq-a-200/8, 6061 t6 federal specification 1st material response or mil-c-11866, 356-t6 military specification 2nd material response
Surface Treatment:
Enamel
Surface Treatment Specification:
Tt-e-489 federal specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-11866 spec.