

View Online at <https://aerobasegroup.com/nsn/5340-00-279-4189>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 0.695 inches and 0.705 inches

**Second Leg Length:**

Between 0.695 inches and 0.705 inches

**Second Leg Width:**

0.500 inches

**First Leg Hole Diameter:**

Between 0.200 inches and 0.210 inches

**Second Leg Hole Diameter:**

Between 0.200 inches and 0.210 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.245 inches and 0.255 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.195 inches and 0.205 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.245 inches and 0.255 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.195 inches and 0.205 inches

**First Leg End Radius:**

0.500 inches

**Second Leg End Radius:**

0.500 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Heat treatment: hardened and tempered

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0