NSN 5340-00-290-4195

Rod End Clevis - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-290-4195

| Thread Class: | | | | | |
|---|--|--|--|--|--|
| 3a rod connection | | | | | |
| Thread Direction: | | | | | |
| Right-hand rod connection | | | | | |
| Thread Length: | | | | | |
| 2.312 inches rod connection | | | | | |
| Shank Length: | | | | | |
| 2.594 inches | | | | | |
| Hole Diameter: | | | | | |
| 0.625 inches | | | | | |
| Shank Diameter: | | | | | |
| Between 0.616 inches and 0.625 inches | | | | | |
| Overall Width: | | | | | |
| 1.062 inches | | | | | |
| End Radius: | | | | | |
| 0.750 inches | | | | | |
| Fork Span Width: | | | | | |
| Between 0.626 inches and 0.634 inches | | | | | |
| Distance From Pivot Pinhole Center To Rod Connection End: | | | | | |
| 3.844 inches | | | | | |
| Fork Arm Thickness: | | | | | |
| 0.219 inches | | | | | |
| Fork Depth: | | | | | |
| 1.000 inches | | | | | |
| Shank Shoulder Diameter: | | | | | |
| 1.438 inches | | | | | |
| Thread Size: | | | | | |
| 0.625 inches rod connection | | | | | |
| Special Features: | | | | | |
| Reyway on shank 0.091 in. Deep by 0.125 in. W by 1.938 in. Lg | | | | | |
| Material: | | | | | |
| Steel comp 4140 | | | | | |
| Material Specification: | | | | | |
| Mil-s-5626 military specification single material response | | | | | |
| Surface Treatment: | | | | | |
| Cadmium | | | | | |
| Style Designator: | | | | | |
| Clevis | | | | | |
| Thread Series Designator: | | | | | |
| Unf rod connection | | | | | |
| Shelf Life: | | | | | |
| N/ | | | | | |

N/a

NSN 5340-00-290-4195

Rod End Clevis - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-5626 spec.