

View Online at <https://aerobasegroup.com/nsn/5340-00-292-5506>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.527 inches and 0.535 inches

Second Leg Length:

Between 0.559 inches and 0.567 inches

Second Leg Width:

2.062 inches

First Leg Hole Diameter:

Between 0.201 inches and 0.208 inches

Second Leg Hole Diameter:

Between 0.127 inches and 0.134 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.686 inches and 0.690 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.688 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.059 inches and 0.067 inches

Second Leg Thickness:

Between 0.059 inches and 0.067 inches

First Leg Width:

2.062 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.057 inches and 1.067 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 8630h

Material Specification:

66 federal standard single material response

Style Designator:

Angle

Fsc Application Data:

Bracket, angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0