

View Online at <https://aerobasegroup.com/nsn/5340-00-298-1430>

First Leg Length:

1.000 inches

Second Leg Length:

2.060 inches

Reinforcement Method (non-core):

Web one side

Second Leg Width:

Between 0.865 inches and 0.875 inches

First Leg Hole Diameter:

Between 0.198 inches and 0.204 inches

Second Leg Hole Diameter:

Between 0.190 inches and 0.395 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.435 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.385 inches and 0.395 inches

First Leg Thickness:

0.094 inches

Second Leg Thickness:

0.094 inches

First Leg Width:

Between 0.865 inches and 0.875 inches

First Leg Distance From Edge To Hole Center Along Width:

0.435 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Right hand installation

Material:

Aluminum alloy

Material Specification:

Ls2454 temper t73 fscm 36659 mfr ref single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Lc+77-2037, class 1, grade a, type 1 fscm 36659 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0