NSN 5340-00-301-3024

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-301-3024 First Leg Length: 1.000 inches Second Leg Length: 2.060 inches Reinforcement Method (non-core): Web both sides Second Leg Width: Between 1.115 inches and 1.125 inches First Leg Hole Diameter: Between 0.390 inches and 0.397 inches Second Leg Hole Diameter: Between 0.190 inches and 0.196 inches Second Leg Distance Between Hole Centers Along Length: 1.000 inches Second Leg Distance From Edge To Hole Center Along Width: 0.500 inches **Second Leg Distance From Edge To Hole Center Along Length:** Between 0.385 inches and 0.395 inches First Leg Thickness: 0.094 inches Second Leg Thickness: 0.094 inches First Leg Width: Between 1.115 inches and 1.125 inches First Leg Distance From Edge To Hole Center Along Width: 0.560 inches First Leg Distance From Edge To Hole Center Along Length: 0.400 inches First Leg Style: Square First Leg Hole Arrangement Style: One hole Second Leg Style: Square Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees

Material:

Aluminum alloy

NSN 5340-00-301-3024 Angle Bracket - Page 2 of 2

No Fiig: A042a0



| Material Specification: |
|--|
| Ls2454-4-15-220, temper t73, fscm 36659 mfr ref single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Lc+77-2037, class 1, grade a, type 1, fscm 36659 mfr ref single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |