

View Online at <https://aerobasegroup.com/nsn/5340-00-305-7342>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

Between 1.122 inches and 1.153 inches

Second Leg Length:

Between 2.292 inches and 2.323 inches

First Leg Hole Diameter:

Between 0.499 inches and 0.501 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

1.208 inches

Second Leg Distance Between Hole Centers Along Length:

1.471 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.297 inches and 0.328 inches

First Leg Thickness:

Between 0.178 inches and 0.208 inches

Second Leg Thickness:

Between 0.178 inches and 0.208 inches

First Leg Width:

Between 0.844 inches and 0.906 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.422 inches and 0.453 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.422 inches and 0.453 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Right hand mounting

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0