NSN 5340-00-305-7343

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-305-7343

Mounting Hole Type:

Countersunk and plain

First Leg Length:

Between 1.122 inches and 1.153 inches

Second Leg Length:

Between 2.292 inches and 2.323 inches

First Leg Hole Diameter:

Between 0.499 inches and 0.501 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

1.208 inches

Second Leg Distance Between Hole Centers Along Length:

1.471 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.297 inches and 0.328 inches

First Leg Thickness:

Between 0.178 inches and 0.208 inches

Second Leg Thickness:

Between 0.178 inches and 0.208 inches

First Leg Width:

Between 0.844 inches and 0.906 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.422 inches and 0.453 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.422 inches and 0.453 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Left hand mounting

NSN 5340-00-305-7343 Angle Bracket - Page 2 of 2

Fiig: A042a0



| Material: |
|--|
| Steel comp 4130 or steel comp 8630 |
| Material Specification: |
| Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |