

View Online at <https://aerobasegroup.com/nsn/5340-00-308-0711>

**First Leg Length:**

0.370 inches

**Second Leg Length:**

0.900 inches

**Second Leg Width:**

0.840 inches

**Second Leg End Width:**

0.300 inches

**First Leg Hole Diameter:**

Between 0.166 inches and 0.169 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.150 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.205 inches

**Second Leg Slot Length:**

0.250 inches

**Second Leg Slot Width:**

0.120 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

0.840 inches

**First Leg Distance Between Hole Centers Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.170 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.170 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

122.0 degrees

**Special Features:**

Secound leg has additional slot, both slots same size, 0.500 in. Cto c on bsc

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, th34 federal specification single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-c-22750, cl 1, type 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.