

View Online at <https://aerobasegroup.com/nsn/5340-00-308-0711>

First Leg Length:

0.370 inches

Second Leg Length:

0.900 inches

Second Leg Width:

0.840 inches

Second Leg End Width:

0.300 inches

First Leg Hole Diameter:

Between 0.166 inches and 0.169 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.150 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.205 inches

Second Leg Slot Length:

0.250 inches

Second Leg Slot Width:

0.120 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

0.840 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.170 inches

First Leg Distance From Edge To Hole Center Along Length:

0.170 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

122.0 degrees

Special Features:

Secound leg has additional slot, both slots same size, 0.500 in. Cto c on bsc

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, th34 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-c-22750, cl 1, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.