

View Online at <https://aerobasegroup.com/nsn/5340-00-316-5865>

First Leg Length:

1.713 inches

Second Leg Length:

3.900 inches

Reinforcement Method (non-core):

Web both sides

Second Leg Width:

3.320 inches

First Leg Hole Diameter:

Between 0.198 inches and 0.204 inches

Second Leg Hole Diameter:

Between 0.198 inches and 0.204 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.934 inches and 1.942 inches

Second Leg Distance Between Hole Centers Along Length:

Between 1.934 inches and 1.942 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.910 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.372 inches

First Leg Thickness:

0.300 inches

Second Leg Thickness:

0.100 inches

First Leg Width:

3.320 inches

First Leg Distance Between Hole Centers Along Width:

1.960 inches

First Leg Distance Between Hole Centers Along Length:

0.913 inches

First Leg Distance From Edge To Hole Center Along Width:

0.680 inches

First Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 310

Material Specification:

Ls2454 t73, fscm 36659 mfr ref single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Lc+77-2037 class 1, grade a, type 1, fscm 36659 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0