

View Online at <https://aerobasegroup.com/nsn/5340-00-324-7700>

First Leg Length:

Between 0.750 inches and 0.780 inches

Second Leg Length:

Between 1.500 inches and 1.550 inches

Second Leg Width:

Between 0.750 inches and 0.780 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.144 inches

Second Leg Hole Diameter:

Between 0.268 inches and 0.271 inches

Second Leg Distance Between Hole Centers Along Length:

Between 1.000 inches and 1.050 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.480 inches and 0.520 inches

First Leg Width:

Between 0.750 inches and 0.780 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between First And Second Hole Centers Along Length:

Between 0.490 inches and 0.510 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

Between 0.490 inches and 0.510 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

Special Features:

Clinch nut on rh side

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-200/3 federal specification single material response or qq-a-250/5 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.