

View Online at <https://aerobasegroup.com/nsn/5340-00-324-7700>

**First Leg Length:**

Between 0.750 inches and 0.780 inches

**Second Leg Length:**

Between 1.500 inches and 1.550 inches

**Second Leg Width:**

Between 0.750 inches and 0.780 inches

**Second Leg Corner Radius:**

Between 0.220 inches and 0.280 inches

**First Leg Hole Diameter:**

Between 0.129 inches and 0.144 inches

**Second Leg Hole Diameter:**

Between 0.268 inches and 0.271 inches

**Second Leg Distance Between Hole Centers Along Length:**

Between 1.000 inches and 1.050 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.480 inches and 0.520 inches

**First Leg Width:**

Between 0.750 inches and 0.780 inches

**First Leg Corner Radius:**

Between 0.220 inches and 0.280 inches

**First Leg Distance Between First And Second Hole Centers Along Length:**

Between 0.490 inches and 0.510 inches

**First Leg Distance Between Second And Third Hole Centers Along Length:**

Between 0.490 inches and 0.510 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**Special Features:**

Clinch nut on rh side

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-200/3 federal specification single material response or qq-a-250/5 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.