

View Online at <https://aerobasegroup.com/nsn/5340-00-329-2040>

Fabrication Method (non-core):

Extruded

Mounting Hole Type:

Countersunk

First Leg Length:

0.550 inches

Second Leg Length:

1.250 inches

Second Leg Width:

2.300 inches

First Leg Hole Diameter:

Between 0.143 inches and 0.149 inches

Second Leg Distance Between Hole Centers Along Width:

0.300 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.550 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.350 inches

First Leg Thickness:

Between 0.044 inches and 0.056 inches

Second Leg Thickness:

Between 0.044 inches and 0.056 inches

First Leg Distance From Edge To Hole Center Along Width:

0.800 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11, t6 federal specification single material response

Surface Treatment:

Primer

Surface Treatment Specification:

Tt-p-1757 federal specification 1st treatment response and mil-c-6183, t 2, cl 1, gr c military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-6183 spec.