

View Online at <https://aerobasegroup.com/nsn/5340-00-330-3564>

**First Leg Length:**

0.2500 inches

**Second Leg Length:**

1.0000 inches

**Second Leg Width:**

0.750 inches

**Second Leg End Width:**

0.562 inches

**First Leg Hole Diameter:**

Between 0.164 inches and 0.169 inches

**Second Leg Hole Diameter:**

Between 0.512 inches and 0.525 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.375 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

0.750 inches

**First Leg End Width:**

0.562 inches

**First Leg Distance Between Hole Centers Along Width:**

0.375 inches

**First Leg Distance Between Hole Centers Along Length:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.188 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

2nd leg has 0.250 in. With slot centered in edge along width through to hole; hole has keyway at 30 degrees angle from center of width at bend

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-318, cond.1/2h military specification single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-15090 type 2 cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

spec.