

View Online at <https://aerobasegroup.com/nsn/5340-00-332-7093>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.660 inches and 0.740 inches

Second Leg Length:

Between 0.660 inches and 0.740 inches

Second Leg Width:

Between 0.360 inches and 0.440 inches

First Leg Hole Diameter:

0.193 inches

Second Leg Hole Diameter:

0.193 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.160 inches and 0.240 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.340 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.360 inches and 0.440 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.160 inches and 0.240 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.340 inches

First Leg End Radius:

0.215 inches

Second Leg End Radius:

0.215 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-3 solution heat treated

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Surface Treatment:

Paint

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0