

View Online at <https://aerobasegroup.com/nsn/5340-00-335-9357>

Fabrication Method (non-core):

Wrought

First Leg Length:

Between 0.913 inches and 0.923 inches

Second Leg Length:

Between 0.945 inches and 0.955 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.260 inches and 0.270 inches

Second Leg Hole Diameter:

Between 0.200 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.245 inches and 0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.195 inches and 0.205 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.245 inches and 0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.225 inches and 0.235 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0