

View Online at <https://aerobasegroup.com/nsn/5340-00-336-1105>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.880 inches

Second Leg Length:

0.880 inches

Second Leg Width:

1.000 inches

Second Leg Hole Diameter:

Between 0.437 inches and 0.444 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Thickness:

0.064 inches

Second Leg Thickness:

0.064 inches

Center Section Height:

0.300 inches

Center Section Width:

1.000 inches

Center Section Thickness:

0.064 inches

First Leg Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg End Radius:

0.810 inches

Second Leg End Radius:

0.810 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

150.0 degrees

Second Leg Angle:

150.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.