NSN 5340-00-336-1105



Double Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-00-336-1105 Fabrication Method (non-core): Stamped First Leg Length: 0.880 inches Second Leg Length: 0.880 inches Second Leg Width: 1.000 inches **Second Leg Hole Diameter:** Between 0.437 inches and 0.444 inches Second Leg Distance From Edge To Hole Center Along Width: 0.500 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.440 inches First Leg Thickness: 0.064 inches **Second Leg Thickness:** 0.064 inches **Center Section Height:** 0.300 inches **Center Section Width:** 1.000 inches **Center Section Thickness:** 0.064 inches First Leg Width: 1.000 inches First Leg Distance From Edge To Hole Center Along Width: 0.500 inches First Leg Distance From Edge To Hole Center Along Length: 0.440 inches First Leg End Radius: 0.810 inches **Second Leg End Radius:** 0.810 inches First Leg Style: End radius First Leg Hole Arrangement Style:

One slot Second Leg Style: End radius **Second Leg Hole Arrangement Style:** One hole

NSN 5340-00-336-1105

Double Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
150.0 degrees
Second Leg Angle:
150.0 degrees
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/5, alclad t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-a-8625 spec.